Godzilla

SUNRISE

NEW



Godzilla Series

Large Dimension Plus Half Cell Mono Solar Module

SR-M660HLP
360~375W

SR-M660360HLP
SR-M660365HLP
SR-M660370HLP
SR-M660375HLP

IEC61215/IEC61730
ISO9001:Quality Management System ISO14001:Environmental Management System
ISO45001:Occupational Health and Safety Management System

PID Resistance

Better Low-light Performance

9 Bus Bar Half Cut Cell With PERC Technology

Strengthened Mechanical Support 5400 Pa Snow Load, 2400 Pa Wind Load

0-3%

0~3% Positive Tolerance

Higher Power Output

Additional value from SUNRISE linear warranty



25 year linear performance warranty from SUNRISE
Standard performance warranty

SUNRISE ENERGY CO., LTD
TEL:+86-519-81688389
Web:www.sunriseenergy.cn
E-mail:info@sunriseenergy.cn
ADD:No.20 Tongzi River West Road, Zhonglou Development Zone, Changzhou, Jiangsu

Large Dimension Plus Half Cell(6x20) Mono Solar Module

Module Type		SR-M660360HLP		SR-M660365HLP		SR-M660370HLP		SR-M660375HLP	
Test Environment		STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Tolerance	(%)	0~+3		0~+3		0~+3		0~+3	
Module Efficiency	(%)	19.46		19.73		20		20.27	
Maximum Power	Pmax(W)	360	266.59	365	270.29	370	273.99	375	277.69
Open Circuit Voltage	Voc(V)	40.92	38.18	41.12	38.38	41.32	38.48	41.56	38.7
Short Circuit Current	Isc(A)	11.22	9.01	11.3	9.07	11.39	9.15	11.46	9.21
Maximum Power Voltage	Vm(V)	33.69	31.08	33.89	31.28	34.09	31.48	34.29	31.66
Maximum Power Current	Im(A)	10.69	8.55	10.78	8.62	10.86	8.69	10.94	8.75
Cell Type	(mm)	166x83(9BB Mono-Crystalline Silicon)							
Number of Cells	(Pcs)	120(6×20)							
Maximum System Voltage	(V)	DC1000							
Temp. Coeff. of Voc	(%/℃)	-0.285							
Temp. Coeff. of Isc	(%/℃)	0.055							
Temp. Coeff. of Pm	(%/℃)	-0.365							
Operating Temperature	℃	-40 to 85							
Nominal Operating Cell Temperature (NOCT)	℃	45±2							
Max. Series Fuse	(A)	15							
Pressure Bearing	(Pa)	5400							
Wind Bearing	(Pa)	2400							

STC: Irradiance 1000W/m^2, Cell temperature 25°C, AM1.5

NOCT: Irradiance 800W/m^2, Ambient temperature 20°C, Wind speed 1m/s

ENGINEERING DRAWINGS



IV CURVES



I-V CURVES OF PV MODULE(370W)



P-V CURVES OF PV MODULE(370W)

Manufactured in China

MATERIAL DETAILS

Frame	Anodized aluminum
Glass	3.2mm low-iron tempered suede glass
Cell	6×20pcs 166x83mm mono solar cell
Junction Box	Rated Current≥15A,IP≥67,TÜV & UL
Cable&Connector	4mm²,MC4 or MC4 compatible
Cable length	1000mm or as customer's requirements

PACKING DETAILS

Dimension	(mm)	1776×1052×35
Weight	(kg)	20
Loading Capacity		832 pcs/40'HC
Packing	pcs/pallet	30

©Sunrise Energy Co., Ltd All rights reserved. Specifications included in this datasheet are subject to change without notice.